

	<b>amh 012</b>	<b>amh 024 / 024-ac amh 024-R (2 chillers)</b>	<b>amh 030 / 030-ac amh 030-R (2 chillers)</b>	<b>amh 032</b>	<b>amh 050 / 060</b>
<b>Max. process water temperature</b>	5 – 40 °C	5 – 60 °C	5 – 60 °C	0 – 40 °C	5 – 60 °C
<b>Cooling power</b>	1,1 kW @ 20 °C	2,4 kW @ 20°C	3,0 kW @ 20°C	3,2 kW @ 20°C	4,7 kW / 6 kW
<b>Pump capacity</b>	1,3 bar @ 7 l/min	Max. 7 bar Typical: 3 bar@13 l/min	Max. 7 bar Typical: 3 bar@13 l/min	Max. 10 bar	Max. 5 bar Typical: 3 bar@20 l/min
<b>Cooling</b>	Water	Water or air (ac)	Water or air (ac)	Water	Water
<b>Operating voltage</b>	1 x 200 – 230 Vac	1 x 200 – 230 Vac	1 x 200 – 230 Vac	1 x 208-230 Vac	1 x 200 – 230 Vac
<b>Dimensions W/D/H</b>	377 / 500 / 615 mm	377 / 500 / 615 mm	377 / 500 / 660 mm	540 / 550 / 713 mm	377 / 592 / 976 mm
<b>Port size – cooling water</b>	R 1/2	G 1/2	G 1/2	G 1/2	G 1/2
<b>Weight</b>	43 kg	43 kg	47 kg	82 kg	67 kg
<b>Remote interface</b>	--	LAM/SPTS	LAM/SPTS	LAM	AMAT Standard P5000/Centura/CHX