

## Jandel RM3000 Test Unit

**JANDEL**



**Jandel Engineering Limited** offers the RM3000 for use in making four point probe measurements. The RM3000 can supply constant currents between 10nA and 99.99mA, and measure voltages from 0.01mV to 1250mV.

For sheet resistance measurements the quoted range is 1 milliohm/square to  $5 \times 10^8$  ohms/square. Measurements outside this range are possible but with possible reduced accuracy.

For volume (bulk) resistivity measurements the quoted range is 1 milliohm.cm to  $1 \times 10^6$  ohm.cm. Measurements outside of this range may be possible but will depend on sample type e.g. whether the sample is a thin layer.

## Jandel RM3000 Test Unit

---

<b>Measurement range</b>	<b>1 ohm/square - 10 Megohms/square, 10 mohm.cm - 10 Kohm.cm</b>
<b>Units</b>	<b>mV ohm/square</b>
<b>Onboard Memory</b>	<b>50 measurements</b>
<b>Software</b>	<b>For operation and data control supplied free of charge</b>
<b>Current</b>	<b>100nA - 10mA, reversible to verify contact and measurement</b>
<b>Accuracy</b>	<b>0.5% across range, better than 0.2% in mid range</b>
<b>Connections</b>	<b>USB</b>

### Unit Selection



Easy unit selection

Measurements can be displayed on screen as mV, ohms/square or ohm.cm. There is a facility to input either probe spacing or wafer thickness so that ohm.cm values can be automatically calculated and displayed.

### Computer connection and Software

The RM3000 can be connected to computer by either USB or RS-232 connection. The customer can operate the unit using the computer keyboard, terminal emulation software such as HyperTerminal, or with the free software provided.